



# Fan-assisted display islands: IDP - IDN

In a competitive market, versatility is everything. The Superette's solution is this incredible island system that can adapt to frozen, chilled or dual-temperature applications. Full vision and a hermetic integral condensing unit make this unit ideal for promotional sales of high-turnover products and impulse sales.



IDP

DIMENSIONS IN mm



IDN

DIMENSIONS IN mm

## APPLICATIONS:

- IDP: Dairy, drinks and deli
- IDN: Frozen food and ice cream
- IDN-B: Dual-temperature freezer/refrigerator

## STANDARD EQUIPMENT:

- Electromechanical control
- Continuous bumper
- Ticket rail
- Night cover (IDN)
- IDN comes with glazed panels and anti-condensation heaters
- IDP comes with Perspex panels
- Adjustable feet

## OPTIONS AND ACCESSORIES:

- Castor kit
- Adjustable grills
- Adaptable to 115V/60Hz
- Wide choice of colours
- Bumpers available in 6 colours
- Adhesive branding

## ISLANDS: IDP / IDN

	IDN-15	IDN-20	IDN-25	IDN-15B	IDN-20B	IDN-25B	IDP-15	IDP-20	IDP-25
<b>Merchandising data</b>									
Length (mm)	1565	2040	2550	1565	2040	2550	1565	2040	2550
Capacity (l)	315	420	525	315	420	525	315	420	525
Net volume (m <sup>3</sup> )	1.52	1.98	2.47	1.52	1.98	2.47	1.45	1.89	2.37
Gross volume (m <sup>3</sup> )	1.92	2.49	3.16	1.92	2.49	3.16	1.84	2.38	3.02
Refrigerated area (m <sup>2</sup> )	1.17	1.56	1.95	1.17	1.56	1.95	1.17	1.56	1.95
Total display area (m <sup>2</sup> )	1.16	1.54	1.93	1.16	1.54	1.93	1.16	1.54	1.93
<b>Electrical data</b>									
Energy consumption (kWh/24h)	27.77	32.35	39.83	11.2(+) 30.8(-)	13.0(+) 31.8(-)	15.7(+) 46.2(-)	5.7	8.6	10.3
Maximum amperage (A)	7.4	10.4	12.7	6.6(+) 7.3(-)	6.0(+) 9.3(-)	7.4(+) 12.6(-)	3.1	4.1	5.5
Sound level (dB)	63	65	65	64(+) 65(-)	64(+) 65(-)	65(+) 65(-)	60	61	61
<b>Refrigeration data</b>									
Climate class	3	3	3	3	3	3	3	3	3
Product temperature class	L3	L3	L3	M2(+) L3(-)	M2(+) L3(-)	M2(+) L3(-)	M2	M2	M2
Refrigerant gas	404A	404A	404A	404A	404A	404A	404A	404A	404A
Refrigerant quantity (g)	600	2X700	2X800	2X650	2X700	2X800	525	750	825
Refrigeration system (static/air cooled)	Air cooled	Air cooled	Air cooled	Air cooled	Air cooled	Air cooled	Air cooled	Air cooled	Air cooled
Automatic defrosting (yes/no)	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes



# A model of versatility